

Verruca and Wart Spray

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBON PROPELLANT	30-60%
CAS number: 68476-85-7	EC number: 270-704-2
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Gas 1 - H220	F+;R12.
Press. Gas, Liquefied - H280	
DIMETHYL ETHER	30-60%
CAS number: 115-10-6	EC number: 204-065-8
	REACH registration number: 01-2119472128-37
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Gas 1 - H220	F+;R12
Press. Gas, Compressed - H280	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing.
Ingestion	Unlikely route of exposure..Do not induce vomiting.Provided the patient is conscious,wash out mouth with water and give 200ml-300ml of water to drink.Obtain immediate medical attention.
Skin contact	If tissues are frozen, do not remove clothes but rinse with plenty of lukewarm water.
Eye contact	Rinse immediately with plenty of water. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	May cause discomfort if swallowed.
Skin contact	The product is considered to be a low hazard under normal conditions of use.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	-----------------------------------------------------

5.2. Special hazards arising from the substance or mixture

Specific hazards	Extremely flammable aerosol. Pressurised container: may burst if heated
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Verruca and Wart Spray

DNEL	Workers - Inhalation; Long term systemic effects: 1894 mg/m ³ Consumer - Inhalation; Long term systemic effects: 471 mg/m ³
PNEC	- Fresh water; 0.155 mg/l - Marine water; 0.016 mg/l - Intermittent release; 1549 mg/l - STP; 160 mg/l - Sediment (Freshwater); 0.681 mg/l - Sediment (Marinewater); 0.069 mg/l - Soil; 0.045 mg/l

8.2. Exposure controls

Hygiene measures Wash hands thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion May cause discomfort if swallowed.

Skin contact Liquid on the skin could result in freeze burns.

Eye contact May cause temporary eye irritation.

SECTION 12: Ecological Information

12.1. Toxicity

Verruca and Wart Spray

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 17/08/2016


Revision 1.0

SDS number 26272

Risk phrases in full R12 Extremely flammable.

Hazard statements in full H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H280 Contains gas under pressure; may explode if heated.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



Signal Word	Danger	
Hazard Statements	H225	Highly flammable liquid and vapour.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
Precautionary Statements	P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P314	Get medical advice/attention if you feel unwell.

2.3. Other hazards

None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Product Name	CARNATION SOOTHING FOOT SPRAY
REACH Registration Number	N/A
CAS-No.	67-63-0
EU Index No.	603-117-00-0
EC No.	200-661-7

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation.

Move the exposed person to fresh air at once. Get medical attention.

Ingestion

Provide rest, warmth and fresh air. Immediately rinse mouth and drink plenty of water (200-300 ml). Get medical attention.

Skin Contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

Eye Contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Hand Protection

Nitrile gloves are recommended.

Eye Protection

Wear approved safety goggles.

Other Protection

Wear rubber apron. Wear rubber footwear.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Odour of alcohol
Solubility	Soluble in water.
Initial Boiling Point and Boiling Range:	82 - 83
Relative Density	0.786 @ 20
Bulk Density	785 kg/m ³
Vapour Density (Air=1)	>1
Vapour Pressure	4.3 kPa 20
Evaporation Rate	1.2
Viscosity	2.65 cSt @ 20
Flash Point (°C)	12
Auto Ignition Temperature (°C)	>350
Flammability Limit - Lower(%)	2.0
Flammability Limit - Upper(%)	12.7

9.2. Other information

Mol. Weight	60
-------------	----

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Hazardous Polymerisation

Will not polymerise.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances. Amides. Aldehydes. Other halogenated organics.

10.6. Hazardous decomposition products

Oxides of: Carbon.

SECTION 11: TOXICOLOGICAL INFORMATION


11.1. Information on toxicological effects

Toxic Dose 1 - LD 50 4700-5500 mg/kg (oral rat)

Toxic Conc. - LC 50 46-73 mg/l/4h (inh-rat)

Inhalation

May cause irritation to the respiratory system. Vapours may cause drowsiness and dizziness.



14.4. Packing group

ADR/RID/ADN Packing group II
IMDG Packing group II
ICAO Packing group II

14.5. Environmental hazards

14.6. Special precautions for user

EMS F-E, S-D
Emergency Action Code +2YE
Hazard No. (ADR) 33
Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I. 2009 No. 716).

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. DSEAR

Guidance Notes

CHIP for everyone HSG(108). Workplace Exposure Limits EH40.

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

Water Hazard Classification

WGK 1

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Risk Phrases In Full

R11 Highly flammable.
R36 Irritating to eyes.
R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

H319 Causes serious eye irritation.
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.